



# United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/634,337	08/04/2003	Bo-Yong Chung	50432/DBP/Y35	6765
23363 CHRISTIE, PA	7590 01/05/2007 ARKER & HALE, LLP		50432/DBP/Y35 6765  EXAMINER  LAO, LUN YI	INER-
PO BOX 7068 PASADENA, CA 91109-7068			LAO, LUN YI	
PASADENA,	CA 91109-7068	•	ART UNIT PAPER NUMBER	PAPER NUMBER
	•		2629	
			<del></del>	
SHORTENED STATUTOR	RY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE	
3 MC	NTHS .	01/05/2007	PAF	PER

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

	Application No.	Applicant(s)	
	10/634,337	CHUNG ET AL.	
Office Action Summary	Examiner	Art Unit	
	LUN-YI LAO	2629	
The MAILING DATE of this communication Period for Reply	appears on the cover sheet w	ith the correspondence address	
A SHORTENED STATUTORY PERIOD FOR REI WHICHEVER IS LONGER, FROM THE MAILING - Extensions of time may be available under the provisions of 37 CFR after SIX (6) MONTHS from the mailing date of this communication If NO period for reply is specified above, the maximum statutory per - Failure to reply within the set or extended period for reply will, by sta Any reply received by the Office later than three months after the may earned patent term adjustment. See 37 CFR 1.704(b).	B DATE OF THIS COMMUNI R 1.136(a). In no event, however, may a iod will apply and will expire SIX (6) MOI atute, cause the application to become A	CATION. reply be timely filed NTHS from the mailing date of this communication BANDONED (35 U.S.C. § 133).	
Status			
1) Responsive to communication(s) filed on 16	6 November 2006.		
·— · · _—	his action is non-final.		
3) Since this application is in condition for allow	wance except for formal mat	ters, prosecution as to the merits is	
closed in accordance with the practice unde	er <i>Ex par</i> te Quayle, 1935 C.[	). 11, 453 O.G. 213.	
Disposition of Claims			
4)⊠ Claim(s) <u>1-34,36 and 37</u> is/are pending in th	ne application.		
4a) Of the above claim(s) <u>35</u> is/are withdraw	• •		
5)⊠ Claim(s) <u>37</u> is/are allowed.			
6)⊠ Claim(s) <u>1-8,11,15-23,25,27-30 and 36</u> is/ai	re rejected.		
7) Claim(s) <u>9,10,12-14,24,26 and 31-34</u> is/are	•		
8) Claim(s) are subject to restriction and			
Application Papers			
9) The specification is objected to by the Exam	iner	•	
10)⊠ The drawing(s) filed on <u>04 August 2003</u> is/ar		piected to by the Evaminer	
Applicant may not request that any objection to t	• • •	· ·	
Replacement drawing sheet(s) including the corr	•	• •	<b>Y</b>
11) The oath or declaration is objected to by the	,	• • •	<i>,</i> ·
Priority under 35 U.S.C. § 119			
12) Acknowledgment is made of a claim for forei	ian priority under 25 H.C.C. I	C 110(a) (d) ar (f)	
a) All b) Some * c) None of:	ight priority under 35 0.5.C.	3 119(a)-(d) or (1).	•
1. Certified copies of the priority docume	ents have been received		
2. Certified copies of the priority docume		application No	
3. Copies of the certified copies of the p		· ·	
application from the International Bure	•	received in this National Stage	
* See the attached detailed Office action for a l	, , , , , , , , , , , , , , , , , , , ,	received.	
Attachment/s\			
Attachment(s)  Notice of References Cited (PTO-892)	4) Intentions	Summary (PTO-413)	
2) DNotice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No(	s)/Mail Date	
3) Information Disclosure Statement(s) (PTO/SB/08)	F	nformal Patent Application	-ten
Paper No(s)/Mail Date <u>11/16/2006</u> .	6) [] Other:	<del></del> ·	

#### **DETAILED ACTION**

### Claim Objections

1. Claims 4-6, 9-10, 22, 24, 31, 34 and 37 are objected to because of the following informalities:

The limitation of "the selection signal" should be changed to -- a selection signal - in claims 4, 9, 22 and 24 since there is no antecedent basis.

The limitation of "a second selection signal" should be changed to -- a first selection signal - in claims 31 and 34, line 3 since there is no a first selection signal in claim 29.

The limitation of "a second selection signal" should be -- changed to a first selection signal – in claim 37, line 18 since there is no a first selection signal in claim 18.

Appropriate correction is required.

## Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

Art Unit: 2629

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

3. Claim 30 is rejected under 35 U.S.C. 102(e) as being anticipated by Kasai(6,989,826).

Kasai teaches a display device comprising: a display element for displaying a portion of an image in response to a current being applied; a first transistor(214) having a main electrode and a control electrode, and coupled between a voltage source(Vdd) and the display element(220); a capacitor(230) coupled between the main electrode and the control electrode of the first transistor(214), a first switching element(213) coupled between the first transistor(214) and the display element(220) to interrupt the current to the display element (220) while charging the capacitor using at least one of a precharge voltage and a data voltage representative of the image portion(220); and a second switching element(211) coupled to a first selection signal(V1); wherein, when the first selection signal(V1) is activated, the second switching element allows the precharge voltage(Vpre) to be applied to the capacitor(230) for charging and the first switching element (213) is turned off to prevent the current from flowing to the display element(220)(see figures 21(a)-22; column 16, lines 32-68 and column 17, lines 1-24).

Art Unit: 2629

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 1-8, 11, 15-23, 25, 27-30 and 36 are rejected under 35 U.S.C. 103(a) as being unpatentable over Gwon(CN 1361510) in view of Kasai(6,989,826).

As to claims 1-8, 11, 15-23, 25, 27-30 and 36, Gwon teaches a display panel for image display, the display panel comprising a plurality of data lines(D1-Dy) for transferring a data voltage representing an image signal, a plurality of scan lines(S1-Sz) for transferring a selection signal, and a plurality of pixel circuits, each pixel circuit being coupled to a corresponding the data line(e.g. D1) and two adjacent the scan lines(Sn and Sn-1), each pixel circuit comprising: a display element capable of displaying a portion of an image, the image portion corresponding to a quantity of applied current; a first transistor(M1) having a main electrode and a control electrode; a capacitor(C1) coupled between the main electrode and the control electrode of the first transistor(M1), wherein the first transistor(M1) is capable of generating the applied current in response to voltage between the main electrode and the control electrode; a second transistor(M2) having a control electrode coupled to the control electrode of the first transistor(M1), the second transistor(M2) being configured to operate as a diode; a first switching element(M3) coupled to a main electrode of the second transistor(M2), wherein the first switching element(M3)

Art Unit: 2629

transfers the data voltage from the data lines(Dm) to the second transistor(M2) in response to the selection signal from one of the two adjacent scan lines(Sn, Sn-1); a second switching element(M4) for transferring a precharge voltage(Vpre) to the control electrode of the first transistor(M1) in response to a first control signal(Sn-1) before the data voltage is supplied(see figures 4, 11B, 12-15, 17 and abstract).

Gwon fails to disclose a third switch for electrically isolating the first transistor from the display element.

Kasai teaches a display panel comprising a third switching element(213) being turned off in response to a second control signal for electrically isolating a first Transistor(214) from a display element(220)(see figure 4-5(d), 22; column 5, lines 60-68 and column 6, lines 1-11). It would have been obvious to have modified Gwon with the teaching of Kasai, so as to improve the display quality by individually controlling a light emitting elements.

As to claim 2, Gwon as modified teach the third switching element(213) is coupled between the first transistor(214) and the display element(220)(see Kasai's figure 4).

As to claim 3, Gwon as modified teach the two adjacent scan

Lines(Sn, Sn-1) comprise a current scan line(Sn) and a previous scan line(Sn-1), and
the one of the two adjacent scan lines(Sn, Sn-1) is the current scan line(Sn)(see

Gwon's figures 4 and 12).

As to claim 4, Gwon as modified teach the first control signal is the selection signal from the previous scan line(Sn-1).

Art Unit: 2629

As to claim 5, Gwon as modified teach the data voltage is applied to the data lines(D1-Dy) after transferring the precharge voltage(Vpre) in response to the first control signal(Sn-1) and before applying the selection signal to the current scan line(Sn)(see figures 11B,12).

As to claim 6, Gwon as modified teach the data voltage in the data lines(D1-Dy) is changed to a desired voltage before the select signal is applied to the current scan line(Sn-1).

As to claims 7 and 8, It would have been obvious to have the second control signal could be the first control signal(Sn-1) since Gwon as modified teach the third switching element is OFF when the second switching element(M4) is ON and the second switching element is PMOST and the third switching element is NMOST(see Gwon's figure 12 and Kasai's figure 4). Therefore, the second control signal could be the first control signal so as to eliminate the control signal lines.

As to claim 11, Gwon as modified teach the third switching element is turned off during a time period of transferring the precharge voltage using the first control signal(Sn-1) and another time period of transferring the data voltage using the selection signal from the current scan line(Sn)(see Gwon's figure 12 and Kasai's figures 4, 12a-12d and 21a-21c; column 11, lines 59-68 and column 12, lines 1-5).

As to claim 15, Gwon as modified teach the first and second switching elements(M1, M2) are transistors of the same type as the first and second transistors(M3, M4, PMOST)(see figure 12).

Art Unit: 2629

As to claim 16, Gwon teaches the precharge voltage(ground voltage) is lower than a lowest data voltage from the data lines(D1-Dy)(see Gwon's figures 4-7; claim 10 or Corresponding US Patent No. 7015,884's figures 6-7; claim 9 and column 7, lines 20-45).

As to claim 17, Gwon as modified teaches a data driver(30) coupled to the display panel(10), the data driver(30) being capable of applying the data voltage to the data lines(D1-Dy); and a scan driver(20) coupled to the display panel(10) and scan driver(20) being capable of applying the selection signal to the scan Lines(see figure 4).

As to claims 18, 19, 27, 29 and 30, Gwon teaches a method for driving an image display device coupled to two adjacent scan(Sn, Sn-1) lines the image display device comprising a first transistor(M1) having a main electrode and a control electrode; a capacitor(C1) coupled between the main electrode and the control electrode of the first transistor(M1), the first transistor(M1) being capable of generating a current corresponding to a voltage charged in the capacitor(C1), a second transistor(M2) having a control electrode coupled to the control electrode of the first transistor(M1) and being configured to operate as a diode, and a display element capable of displaying a portion of an image corresponding to a quantity of the current generated by the first transistor(M1), the method comprising: transferring a precharge voltage(Vpre) to the control electrode of the first transistor(M1) in response to a first control signal(Sn-1)during a first time period; transferring a data voltage to the control

Art Unit: 2629

electrode of the first transistor(M1) through the second transistor(M2) in response to a selection signal from one of the two adjacent scan lines(Sn-1, Sn) during a second time period; (see figures 4, 11B, 12-15, 17 and abstract).

Gwon fails to disclose a method for interrupting the transfer of data voltage and switching means(claim 27) or first switching element(claims 29 and 30) for electrically isolating the first transistor from a display element during at least one of the first time period and the second time period.

Kasai teaches a display panel comprising switching means or first switching element(213) for interrupting the being turned off in response to a second control signal for electrically isolating a first transistor(214) from a display element(220) during at least one of a first time period(Tc, precharge period) and a second time period(data transferring period(Im) (see figure 4-5(d), 22; column 5, lines 60-68 and column 6, lines 1-11). It would have been obvious to have modified Gwon with the teaching of Kasai, so as to improve the display quality by individually controlling a light emitting elements.

As to claim 20, Gwon as modified teach the two adjacent scan lines(Sn, Sn-1) comprise a current scan line(Sn) and a previous scan line(Sn-1), and the one of the two adjacent scan lines(Sn, Sn-1) is the current scan line(Sn)(see Gwon's figures 4 and 12).

As to claims 21 and 28, Gwon as modified teach the first control signal is the selection signal from the previous scan line(Sn-1).

Art Unit: 2629

As to claim 22, Gwon as modified teach the first transistor(M1) is electrically isolated from the display element(OLED) in response to the selection signal from the previous scan line(Sn-1) during the second time period(transferring data voltage period)(see Gwon's figure 12 and Kasai's figure 4, 21a-21c and column 16, lines 32-39).

As to claim 23, Gwon as modified teach the first transistor(M1) is electrically isolated from the display element(OLED) in response to a second control signal(V2) during the second time period(transferring data voltage period)(see Gwon's figure 12 and Kasai's figure 4, 21a-21c and column 16, lines 32-39).

As to claim 25, Gwon as modified teach a method for preventing the precharge voltage(Vpre) and the data voltage from being transferred to the control electrode of the first transistor(M1) between the first and second time periods(precharging period and transferring data voltage period)( see Gwon's figure 12 and Kasai's figure 4, 21a-21c and column 16, lines 32-39).

As to claim 36, Gwon teach a second transistor(M2)(see figure 12).

## Allowable Subject Matter

6. Claims 9-10, 12-14, 24, 26 and 31-34 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Application/Control Number: 10/634,337 Page 10

Art Unit: 2629

7. Claim 37 is allowable since none of cited references teach a display device comprising a second switching element(M3) coupled to a second selection signal(Sn), when the second selection signal is activated, the second switch(M3) allows the data voltage to be applied to the capacitor(Cst) for charging and the first switching element(M5) is turned off to prevent the current from to the display element(OLED)(see figures 4 and 7), with all other limitation cited in claim 37.

#### Conclusion

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Lun-yi Lao whose telephone number is 571-272-7671. The examiner can normally be reached on M-F.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Bipin Shalwala can be reached on 571-272-7681. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/634,337 Page 11

Art Unit: 2629

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

December 20, 2006

Primary Examine